



New For 2007

VMC's new DV Pro Media Player economically adds multimedia capability to the VM-3.



The DV Pro Media Player

Playable formats:	MPEG-1 video (Video CD) MPEG-2 video (DVD)* MPEG-4 video (DivX format) MPEG still picture MP3 audio JPEG still picture VGA (640x480)
Video Storage medium:	CompactFlash Memory Cards : Type 1 & Type 2
Output Display Systems:	TV and Video Monitors VGA monitors
Video Output:	Signal type : Composite and S-Video Output format : PAL and NTSC
Output Resolution:	Low resolution : 352 x 288 pixels (PAL) : 352 x 240 pixels (NTSC) High resolution : 720 x 576 pixels (PAL) : 720 x 480 pixels (NTSC) Still picture : 704 x 576 pixels (PAL) : 704 x 480 pixels (NTSC) JPEG picture : 800 x 600 pixels
Audio Outputs:	Stereo output, connector – RCA jack, 3.2 V p-p max. 5K ohm
Signal-to-Noise:	96 dB
Select Switches:	Power ON/OFF switch PAL/NTSC playback format select Video / VGA select
Indicators:	Power LED, Status LED
Start-up Modes:	Autoplay (at power-on); Sleep mode (after power-on)
Power Input:	12V DC, 500mA typical
Power Consumption:	6 W
Environment:	0 °C to 50 °C , free air circulation
Relative Humidity	5-95% relative humidity, non-condensing
Dimensions:	165.6 x 38 x 107mm (W x H x D)
Weight :	net weight: 300g
External ports:	RS-232 port – for barcode application (Baud rate: 9600, n,8,1). Record suffix = CR (0D Hex) Remote Ext. – External buttons connection (8-buttons) USB port – USB Host
Video Storage Accessories:	CompactFlash Card – various memory capacities available 128, 256, 512MB, 1G, 2G, 4G